

## 45° VERSA BAR

### SPECIFICATION:

<b>Input Voltage</b>	12VDC or 24VDC
<b>CRI</b>	80+
<b>Dimmable</b>	0-10V, ELV, MLV
<b>Color Temp</b>	<div style="display: flex; justify-content: space-around;"> <div style="width: 15px; height: 15px; background-color: #f9c79f; border: 1px solid black;"></div> 3000K  <div style="width: 15px; height: 15px; background-color: #a2c4c9; border: 1px solid black;"></div> 4000K  <div style="width: 15px; height: 15px; background-color: #74a9cf; border: 1px solid black;"></div> 6250K                 </div>
<b>Max Run</b>	4.9 ft/driver
<b>IP Rating</b>	IP50 - damp locations
<b>Mounting</b>	Screws and mounting clips included
<b>Connectors</b>	All 45° Versa Bars have a mini female barrel connector on both ends.
<b>Dimensions</b>	W 1.3" (33mm) x H 0.73" (8.2mm)
<b>Finish</b>	Silver
<b>Lens</b>	Frosted or Clear
<b>Warranty</b>	1 year limited



### Accessories included:

Screws, mounting clips, 45° Versa-to-45° Versa connector, and 6" 45° Versa-to-standard female barrel connector

### Certifications:



### WATTAGE & LIGHT OUTPUT:

LENGTH	WATTAGE	WW LUMEN OUTPUT		NW LUMEN OUTPUT		CW LUMEN OUTPUT	
		Clear	Frosted	Clear	Frosted	Clear	Frosted
12in	3W	250 lm	200 lm	250 lm	200 lm	250 lm	200 lm
20in	5W	420 lm	350 lm	420 lm	350 lm	420 lm	350 lm
40in	11W	820 lm	720 lm	820 lm	720 lm	820 lm	720 lm

### PART NUMBER BUILDER / ORDERING GUIDE

Example part number: V2F45D20WW12V

